

Distribution of Houses by Predominant Materials of Roof and Wall and Level of Damage Risk

Table No. : CT 17

State : CHHATTISGARH

DAKSHIN BASTAR DANTEWADA

Wall / Roof		Census Houses		Level of Risk under								Flood Prone Area in %
		No. of Houses	%	EQ Zone				Wind Velocity m/s				
				V	IV	III	II	55 & 50	47	44 & 39	33	
				Area in %				Area in %				
						.1	99.9			100		
WALL												
A1 - Mud & Unburnt Brick Wall	Rural	83,898	65.6									
	Urban	8,823	6.9									
	Total	92,721	72.5			M	L			M		
A2 - Stone Wall not packed with mortar	Rural	186	0.1									
	Urban	139	0.1									
	Total	325	0.2			M	L			L		
Total - Category - A		93,046	72.7									
B - Burnt Bricks Wall & Stone wall packed with mortar	Rural	9,582	7.5									
	Urban	14,305	11.2									
	Total	23,887	18.7			L	VL			L		
Total - Category - B		23,887	18.7									
C1 - Concrete Wall	Rural	218	0.2									
	Urban	195	0.2									
	Total	413	0.4			VL	VL			VL		
C2 - Wood wall	Rural	3,876	3.0									
	Urban	1,048	0.8									
	Total	4,924	3.8			VL	VL			M		
Total - Category - C		5,337	4.2									
X - Other Materials	Rural	3,770	2.9									
	Urban	1,877	1.5									
	Total	5,647	4.4			VL	VL			M		
Total - Category - X		5,647	4.4									
TOTAL HOUSES*		127,917										

ROOF												
R1 - Light Weight Sloping Roof	Rural	23,331	18.2									
	Urban	9,818	7.7									
	Total	33,149	25.9			L	VL			H		
R2 - Heavy Weight Sloping Roof	Rural	74,025	57.9									
	Urban	8,750	6.8									
	Total	82,775	64.7			L	VL			L		
R3 - Flat Roof	Rural	4,174	3.3									
	Urban	7,819	6.1									
	Total	11,993	9.4	<i>Damage Risk as per that for the Wall supporting it</i>								
TOTAL HOUSES*		127,917										

Probable Maximum Precipitation at a Station of the district in one day for arial extent of 1000 sqm. **703 mm**

Housing Category : Wall Types

Category - A : Buildings in field-stone, rural structures, unburnt brick houses, clay houses

Category - B : Ordinary brick building; buildings of the large block & prefabricated type, half-timbered structures, building in natural hewn stone

Category - C : Reinforced building, well built wooden structures

Category - X : Other materials not covered in A,B,C. These are generally light.

Notes : 1. Flood prone area includes that protected area which may have more severe

damage under failure of protection works. In some other areas the local damage may be severe under heavy rains and choked drainage.

2. Damage Risk for wall types is indicated assuming heavy flat roof in categories A, B and C (Reinforced Concrete) building

3. Source of Housing Data : Census of Housing, GOI, 2011

Housing Category : Roof Type

Category - R1 - Light Weight (Grass, Thatch, Bamboo, Wood, Mud, Plastic, Polythene, GI Metal, Asbestos Sheets, Other Materials)

Category - R2 - Heavy Weight (Tiles, Stone/Slate)

Category - R3 - Flat Roof (Brick, Concrete)

EQ Zone V : Very High Damage Risk Zone (MSK > IX)

EQ Zone IV : High Damage Risk Zone (MSK VIII)

EQ Zone III : Moderate Damage Risk Zone (MSK VII)

EQ Zone II : Low Damage Risk Zone (MSK < VI)

Level of Risk : VH = Very High; H = High;

M = Moderate; L = Low; VL = Very Low

* Total No. of Houses excluding Vacant/Locked Houses