

Distribution of Houses by Predominant Materials of Roof and Wall and Level of Damage Risk

Table No. : OR 18

State : ODISHA

PURI

Wall / Roof		Census Houses		Level of Risk under									
		No. of Houses	%	EQ Zone				Wind Velocity m/s				Flood Prone Area in %	
				V	IV	III	II	55 & 50	47	44 & 39	33		
				Area in %				Area in %					
						75.3	24.7	100					32.5
WALL													
<i>A1 - Mud & Unburnt Brick Wall</i>	Rural	141,284	31.4										
	Urban	5,480	1.2										
	Total	146,764	32.6					<i>M</i>	<i>L</i>	<i>VH</i>			<i>VH</i>
<i>A2 - Stone Wall not packed with mortar</i>	Rural	6,814	1.5										
	Urban	993	0.2										
	Total	7,807	1.7					<i>M</i>	<i>L</i>	<i>H</i>			<i>VH</i>
Total - Category - A		154,571	34.3										
<i>B - Burnt Bricks Wall & Stone wall packed with mortar</i>	Rural	186,976	41.5										
	Urban	51,826	11.5										
	Total	238,802	53.0					<i>L</i>	<i>VL</i>	<i>H</i>			<i>H/M</i>
Total - Category - B		238,802	53.1										
<i>C1 - Concrete Wall</i>	Rural	2,725	0.6										
	Urban	2,841	0.6										
	Total	5,566	1.2					<i>VL</i>	<i>VL</i>	<i>L</i>			<i>L/ VL</i>
<i>C2 - Wood wall</i>	Rural	6,579	1.5										
	Urban	1,562	0.3										
	Total	8,141	1.8					<i>VL</i>	<i>VL</i>	<i>VH</i>			<i>H</i>
Total - Category - C		13,707	3.0										
<i>X - Other Materials</i>	Rural	39,289	8.7										
	Urban	3,662	0.8										
	Total	42,951	9.5					<i>VL</i>	<i>VL</i>	<i>VH</i>			<i>VH</i>
Total - Category - X		42,951	9.5										
TOTAL HOUSES*		450,031											

ROOF													
<i>R1 - Light Weight Sloping Roof</i>	Rural	285,650	63.5										
	Urban	29,914	6.6										
	Total	315,564	70.1					<i>L</i>	<i>VL</i>	<i>VH</i>			<i>VH</i>
<i>R2 - Heavy Weight Sloping Roof</i>	Rural	7,098	1.6										
	Urban	1,425	0.3										
	Total	8,523	1.9					<i>L</i>	<i>VL</i>	<i>H</i>			<i>H</i>
<i>R3 - Flat Roof</i>	Rural	90,919	20.2										
	Urban	35,025	7.8										
	Total	125,944	28.0	<i>Damage Risk as per that for the Wall supporting it</i>									
TOTAL HOUSES*		450,031											

Probable Maximum Precipitation at a Station of the district in one day for arial extent of 1000 sqm. 801 mm

Housing Category : Wall Types

Category - A : Buildings in field-stone, rural structures, unburnt brick houses, clay houses

Category - B : Ordinary brick building; buildings of the large block & prefabricated type, half-timbered structures, building in natural hewn stone

Category - C : Reinforced building, well built wooden structures

Category - X : Other materials not covered in A,B,C. These are generally light.

Notes : 1. Flood prone area includes that protected area which may have more severe damage under failure of protection works. In some other areas the local damage may be severe under heavy rains and choked drainage.

2. Damage Risk for wall types is indicated assuming heavy flat roof in categories A, B and C (Reinforced Concrete) building

3. Source of Housing Data : Census of Housing, GOI, 2011

Housing Category : Roof Type

Category - R1 - Light Weight (Grass, Thatch, Bamboo, Wood, Mud, Plastic, Polythene, GI Metal, Asbestos Sheets, Other Materials)

Category - R2 - Heavy Weight (Tiles, Stone/Slate)

Category - R3 - Flat Roof (Brick, Concrete)

EQ Zone V : Very High Damage Risk Zone (MSK > IX)

EQ Zone IV : High Damage Risk Zone (MSK VIII)

EQ Zone III : Moderate Damage Risk Zone (MSK VII)

EQ Zone II : Low Damage Risk Zone (MSK < VI)

Level of Risk : VH = Very High; H = High;

M = Moderate; L = Low; VL = Very Low

* Total No.of Houses excluding Vacant/Locked Houses