

Distribution of Houses by Predominant Materials of Roof and Wall and Level of Damage Risk

Table No. : AS 03

State : ASSAM

GOALPARA

Wall / Roof		Census Houses		Level of Risk under									Flood Prone Area in %
		No. of Houses	%	EQ Zone				Wind Velocity m/s					
				V	IV	III	II	55 & 50	47	44 & 39	33		
				Area in %				Area in %					
				100				73.1	26.9			.8	
WALL													
A1 - Mud & Unburnt Brick Wall	Rural	5,354	2.0										
	Urban	615	0.2										
	Total	5,969	2.2	VH				VH	H			VH	
A2 - Stone Wall not packed with mortar	Rural	933	0.4										
	Urban	441	0.2										
	Total	1,374	0.6	VH				H	M			VH	
Total - Category - A		7,343	2.8										
B - Burnt Bricks Wall & Stone wall packed with mortar	Rural	34,964	13.4										
	Urban	14,075	5.4										
	Total	49,039	18.8	H				H	M			H/M	
Total - Category - B		49,039	18.7										
C1 - Concrete Wall	Rural	6,405	2.4										
	Urban	2,469	0.9										
	Total	8,874	3.3	M				L	VL			L/ VL	
C2 - Wood wall	Rural	4,365	1.7										
	Urban	758	0.3										
	Total	5,123	2.0	M				VH	H			H	
Total - Category - C		13,997	5.4										
X - Other Materials	Rural	172,310	65.9										
	Urban	18,907	7.2										
	Total	191,217	73.1	M				VH	H			VH	
Total - Category - X		191,217	73.1										
TOTAL HOUSES*		261,596											

ROOF												
R1 - Light Weight Sloping Roof	Rural	221,012	84.5									
	Urban	35,782	13.7									
	Total	256,794	98.2	M				VH	VH			VH
R2 - Heavy Weight Sloping Roof	Rural	2,547	1.0									
	Urban	452	0.2									
	Total	2,999	1.2	H				H	M			H
R3 - Flat Roof	Rural	772	0.3									
	Urban	1,031	0.4									
	Total	1,803	0.7	Damage Risk as per that for the Wall supporting it								
TOTAL HOUSES*		261,596										

Probable Maximum Precipitation at a Station of the district in one day for areal extent of 1000 sq.km. is 732 mm

Housing Category : Wall Types

Category - A : Buildings in field-stone, rural structures, unburnt brick houses, clay houses

Category - B : Ordinary brick building; buildings of the large block & prefabricated type, half-timbered structures, building in natural hewn stone

Category - C : Reinforced building, well built wooden structures

Category - X : Other materials not covered in A,B,C. These are generally light.

Notes : 1. Flood prone area includes that protected area which may have more severe damage under failure of protection works. In some other areas the local damage may be severe under heavy rains and choked drainage.

2. Damage Risk for wall types is indicated assuming heavy flat roof in categories A, B and C (Reinforced Concrete) building

3. Source of Housing Data : Census of Housing, GOI, 2011

Housing Category : Roof Type

Category - R1 - Light Weight (Grass, Thatch, Bamboo, Wood, Mud, Plastic, Polythene, GI Metal, Asbestos Sheets, Other Materials)

Category - R2 - Heavy Weight (Tiles, Stone/Slate)

Category - R3 - Flat Roof (Brick, Concrete)

EQ Zone V : Very High Damage Risk Zone (MSK > IX)

EQ Zone IV : High Damage Risk Zone (MSK VIII)

EQ Zone III : Moderate Damage Risk Zone (MSK VII)

EQ Zone II : Low Damage Risk Zone (MSK < VI)

Level of Risk : VH = Very High; H = High;

M = Moderate; L = Low; VL = Very Low

* Total No.of Houses excluding Vacant/Locked Houses